

Opti[®] 200 Shrink Film

Cross-linked multi-purpose strength film for a broad range of applications



Benefits

- SUPERIOR OPTICS
- TOUGH
- VERSATILE
- FLEXIBLE
- USER FRIENDLY
- FDA APPROVED
- RECYCLABLE
- AVAILABLE IN CENTERFOLD ONLY

Opti® 200 Properties

Opti [®] 200 Properties		ASTM	Typical Values			
		Test Method	MAX		STD	DUR
Haze (%)		D 1003-95	2.2	3.2	3.4	
Gloss (%)		D 2457-90	91.6	85	85	
Clarity (%)		D 1746-92	81.3	85	85	
Instrumented Impact Strength (Lb.)		D 3763-95a	12.0	17.5	19.9	
Coefficient of Friction (film-to-film, kinetic)		D 1894-95	0.33	0.30	0.30	
Water Vapor Transmission Rate (gms/100sq. In./24hrs.)		F 1249-90	1.7	1.6	1.3	
Oxygen Transmission Rate (cc/m ² / 24 hrs. @ 73 °F., 1atm)		D 3985-95	6300	7870	6370	
Tear Propagation (gms)	LD* / TD**	D 1938	2.7 / 3.3	3.6 / 3.8	4.6 / 4.7	
Elongation at Break (%)	LD* / TD**	D 882-95	65 / 95	69 / 110	89 / 90	
Minimum Use Temperature			-60 °F			
Maximum Storage Temperature			90 °F			
			LD*	TD**	LD*	TD**
Tensile Strength (psi)		D 882-95	18,000	19,000	17,500	19,000
Modulus of Elasticity (psi @ 73 °F)		D 882-95	63,400	57,000	60,000	65,000
Free Shrink (%)		D 2732-83				
	@180 °F		6.5	8	8	11
	@200 °F		10.5	13.5	13	20
	@220 °F		21	29.5	26	34
	@240 °F		51	55	65	65
	@260 °F		51	57	80	78
Shrink Tension (psi)		D 2838-95				
	@200 °F		423	479	420	530
	@220 °F		531	534	490	530
	@240 °F		551	466	560	540
	@260 °F		555	386	556	490

* Longitudinal Direction ** Transverse Direction

This information represents our best judgement based on the work done, but the Company assumes no liability whatsoever in connection with the use of information or findings contained herein. Opti® Max shrink film complies with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, for the packaging of all foods, with the exception of high alcoholic, at temperatures of 65 °C and below.



Sealed Air Africa (Pty) Ltd.
+27 11 923 4600 Fax: +27 11 392 1025

Sealed Air Australia Ltd.
1 800 0808 481 Fax: 1 800 250 650

Sealed Air Packaging (Shanghai) Co. Ltd.
+86 21 3920 2988 Fax: +86 21 3920 2999

Diversey Gulf FZE
+971 4 8819470/31 Fax: +971 4 8819488

Sealed Air Hong Kong Ltd.
+852 2178 7876 Fax: +852 2407 3385

Sealed Air (India) Private Ltd.
+91 80 4050 7333 Fax: +91 80 4117 1301

Sealed Air HK Ltd. - Indonesia Rep Office
+62 21 5793 8858 Fax: +62 21 5793 8859

Sealed Air (Israel) Ltd.
+972 2 5337438 Fax: +972 2 5337439

Sealed Air (Japan) Ltd.
+81 3 5644 1110 Fax: +81 3 5644 1160

Diversey Eastern and Central Africa Ltd. (Kenya)
+254 703 040 247 Fax: +254 703 040 888

Sealed Air (Korea) Ltd.
+82 31 763 1716 Fax: +82 31 763 4744

Sealed Air (Malaysia) Sdn Bhd
+60 3 5569 6363 Fax: +60 3 5569 2682

Diversey Maroc s.a. (Morocco)
+212 522 756 506 Fax: +212 522 756 572/73

Sealed Air New Zealand
+64 9 813 9800 Fax: +64 9 813 9801

Diversey West Africa Limited (Nigeria)
+234 1 825 5511 Fax: +234 813 086 5000-6

Sealed Air Philippines, Inc.
+63 2 845 9400 Fax: +63 2 2811 6679

Diversey KSA - Arabian Modern Company (Saudi Arabia)
+966 3 847 6986-7 Fax: +966 3 847 6989

Sealed Air (Singapore) Pte. Ltd.
+65 6861 1828 Fax: +65 6861 5221

Sealed Air (Taiwan) Ltd.
+886 3 324 2988 Fax: +886 3 324 3088

Sealed Air (Thailand) Ltd.
+66 2 834 6800 Fax: +66 2 834 6888

Diversey Kimya Sanayi ve Ticaret A.S. (Turkey)
+90 216 578 6400 Fax: +90 216 578 6401

Sealed Air (Singapore) Pte. Ltd. - Vietnam Rep Office
+84 8 6292 4251 Fax: +84 8 6296 2606

Corporate Offices: Sealed Air Corporation

200 Riverfront Blvd, Elmwood Park, NJ 07407 www.sealedair.com

© Reg. U.S. Pat. Off. © Sealed Air Corporation 2013. All Rights Reserved. Printed in the USA.
The "9 Dot Logo" and "Sealed Air" are registered trademarks of Sealed Air Corporation (US).